

## COMBINED SOUNDER STROBE

### FLASHNI

- Operating voltage 18-28VDC
- High output sounder beacon
- Volume control
- Lockable base standard
- Deep base available for IP65



### BEL-SBSB(RED)

- Banshee Excel lite (BEL-SBSB) An Electronic Conventional Sounder Beacon which can be installed internally.
- Low current consumption
- Easy to install
- Maximum 110dB(A) at 1m (dependant on tone selected)
- 32 user-selectable tones



### BEACON-WB-R

- Deep base for FLASHNI
- IP65
- Picture shows Flashni with BEACON-WB-R fitted



IP RATED

### BEL-SBDB(RED)

- Banshee Excel Lite IP66 (BEL-SBDB) An Electronic Conventional Sounder Beacon comes with a deeper IP66 back box, which enables the unit to be installed externally.
- Low current consumption
- Easy to install
- Maximum 110dB(A) at 1m (dependant on tone selected)
- 32 user-selectable tones



IP RATED

## Generic Warning Signs

### Product Overview

"EXTINGUISHING SYSTEM INOPERATIVE"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA

WS-GEN-ESI



### Product Overview

"FIRE ALARM/DO NOT ENTER"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA

WS-GEN-FA/  
DNE



### Product Overview

"FIRE ALARM/EVACUATE AREA"

- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA

WS-GEN-FA  
/EVAC



### Product Overview

"FIRE ALARM/EVACUATE AREA"  
(Weatherproof)

- IP 55
- High brightness white LED's
- Split level function - programmable
- 2 wire reverse polarity input
- Internal buzzer with disable
- 300W x 195H x 50D (mm)
- 15-30VDC / 130mA /

WS-GEN-FA/  
DNE - WP



### Flush Surround

Available for all non-weatherproof warning signs



(KM-FS-WS)